JOEL RIGGING LANYARDS

Connecting you safely. Lanyards are engineered products, and the critical connection component between the full body harness and the anchor. They are sometimes referred to as connectors. Our lanyards are designed and tested to comply to strict CSA standards. JOEL RIGGING offers a wide variety of lanyards to suit a wide range of applications.

The Standard configuration comes with:

FEATURES

- Approved for use in vertical and horizontal applications
- Tested and approved for foot level tie-off
- Additional testing over alternate leading edge materials
- Carabiner hook included for attachment to anchor point
- Aluminum housing for maximum durability
- 3/16" (5mm) galvanized cable lifeline
- LE minimum fall clearance: 13 ft. (4m)
- Certified to CSA Z259.2.2-98 for non-Leading Edge applications



JOEL RIGGING supplies life safety equipment for working at heights in addition to designing and installing the infrastructure required for attaching this equipment to. Call us for additional information.

TECHNICAL DATA

Product N°	Model N°	Lifeline Type	Length	Weight	Hook Style	Capacity
V8455330	SRL-53302-20LE	3/16" (5mm)	20' (6m)	7 lbs. (3 kg)	3/4" Snap Hook	300 lbs. (136kg)



1-905-890-8802 | **JOELTHEATRICAL.COM**





